CONTROL BOX/ COMPACT SERVOMOTOR UNIT SC-910/M91

Reliability of control box and motor has been further improved thanks-to-the-advancement of our accumulated technology.



SC-910 model control box is resistant to voltage fluctuations. It comes with a compact and energy-saving type switching power supply system that does not use a transformer. This contributes to improved reliability.

The M91 model compact motor unit featuring low vibration and low noise capabilities is installed on the control box.

The number of revolutions can be selected from among three different types (standard, slow and fast) according to the preference of the operator. In addition to this feature, the control box incorporates many different functions for upgraded workability.

DDL-8700-7/CP-160A







APPLICABLE MODELS

Applicable models of SC910/M91 are as follows,

1-needle, Lockstitch Machine with Automatic Thread Trimmer	1-needle, Lockstitch Zigzag Stitching Machine with Automatic Thread Trimmer	
DDL-5550N-7	LZ-2282N-7 (standard zigzag with lower knife)	
DDL-8700-7	LZ-2284N-7 (standard/3-step zigzag)	
DLN-5410N-7 (needle-feed)	LZ-2284NU-7 (standard/3-step zigzag with anti-material-slip capability)	
DLU-5490N-7 (bottom and variable top-feed)	LZ-2284C-7 (cylinder-bed, standard/3-step zigzag)	
DLD-5430N-7 (differential-feed)	2-needle, Lockstitch Machine with Automatic Thread Trimmer	
DLM-5400N-7 (with vertical edge trimmer)	LH-3128-7 (needle-feed)	
DMN-5420N-7 (needle-feed with vertical edge trimmer)	LH-3168-7 (needle-feed with organized split needle bar)	
DDL-5600N-7 (double-capacity hook)	LH-3178-7 (needle-feed with large hooks)	
DLN-5410NJ-7 (needle-feed with double-capacity hook, for jeans)	LH-3188-7 (needle-feed with organized split needle bar and large hooks)	

APPLICABLE OPERATION PANELS

Operation panels can be selected in accordance with operation and use.



IP-100

- The operation panel has been provided with a large user-friendly LCD. A pictograph and set values are shown on the same screen, which promises improved operability of the panel.
- The operation panel has been provided with a variety of communication and maintenance control features and is able to store data on a SmartMedia or personal computer.
- The features of the operation panel can be updated without the need for changing the PWB/ROM.

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

PSC box

Motor for SC

Pulley belt

Standard

PSC box			Code
For JUS (LA)*	Single-phase	100~120V	S
For JUS*, General Export	3-phase	200~240V	D
For General Export	Single-phase	200~240V	K
For EU (CE)	Single-phase	200~240V	N
For China	Single-phase	200~240V	U

Control boxCodeStandardSProvided with built-in I/O boardA*

Pattern sewing can be performed by the

Four different kinds of pattern sewing are

possible: automatic reverse stitching, constant-

dimension sewing, rectangle-shape sewing,

The maximum number of stitches that can be

set for automatic reverse stitching (single or

number of stitch control feature.

and multi-layer stitching.

double) is 19.

CP-160

*Please choose code A to equip the remaining bobbin thread detector (AE-4, AE-5) with 1-needle lockstitch machine with automatic thread trimmer.

*JUS: North America and Central and South America.

Code

Operation panel

Model name	Operation panel		
Widder hame	IP-100	CP-160	
1-needle, lockstitch machine	IP-100C	CP-160A	
Zigzag stitching machine	IP-100B	CP-160B	
2-needle, lockstitch machine	IP-100B	CP-160B	

SC910



UKI CORPORATION HEAD OFFICE he environmental management system to promote and conduct the technological and technical research, the development and design of the products in which the environmental impact is considered, the conservation of the energy and resources, and the recycling.

in the research, development, design, distribution, sale and maintenance service of the industrial serving machines, household serving machines and industrial-use robots, etc. and in the purchase, distribution and sale of the household commodities including the healthcare products.

• To order, please contact your nearest JUKI distributor.



8-2-1, KOKURYO-CHO, CHOFU-SHI, TOKYO 182-8655, JAPAN PHONE : (81) 3-3480-2357, 2358 FAX : (81) 3-3430-4909, 4914 http://www.juki.com

* Specifications and appearance are subject to change without prior notice for improvement. * Read the instruction manual before putting the machine into service to ensure safety.